



MANUFACTURERS SAFETY DATA SHEET

Faux Real Mineral Paint

1 | IDENTIFICATION OF THE SUBSTANCE/MIXTURE & OF THE COMPANY/UNDERTAKING

1.1 | PRODUCT IDENTIFIER

Code None
Product name Faux Real Mineral Paint

1.2 | RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE & USES ADVISED AGAINST

Intended use Paint For Interior

1.3 | DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name Faux Real Paint Company – Eco-Sustainable Building Technologies
Full Address 136 Eugene Street
District & Country Gibsonville, NC 27249 | United States of America (USA)
336-447-1000

1.4 | EMERGENCY TELEPHONE NUMBER

For urgent inquiries refer to Call 911 if you have a poison emergency.
Call the CDC if swallowed but person is alert 1-800-222-1222

2 | Hazards identification

2.1 | CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

The product is classified as hazardous pursuant to the provisions set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety data sheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Danger symbols Xi
R Phrases 36/38

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

2.2 | LABEL ELEMENTS

Hazard labeling pursuant to Directives 67/548/EEC and 1999/45/EC and subsequent amendments and supplements.

R36/38 Irritating To Eyes And Skin.
S2 Keep Out Of The Reach Of Children.
S25 Avoid Contact With Eyes.
S26 In Case Of Contact with Eyes, Rinse Immediately with



MANUFACTURERS SAFETY DATA SHEET

Faux Real Mineral Paint

- S37** Plenty of Water and Seek Medical Advice.
- S37** Wear Suitable Gloves.
- S46** If Swallowed, Seek Medical Advice Immediately and Show this Container or Label.



2.3 | **OTHER HAZARDS**
Information not available.

3 | **COMPOSITION/INFORMATION ON INGREDIENTS**

3.1 | **SUBSTANCES**
Information not relevant.

3.2 | **MIXTURES**

IDENTIFICATION	CONC. %	CLASSIFICATION 67/548/EEC	CLASSIFICATION 1272/2008
SILICIC ACID, POTASSIUM SALT			
CAS. 1312-76-1	2 - 2.2	Xi R36/38	Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC. 215-199-1			
INDEX -			
Reg. No. 01-2119456888-17			

T+ = Very Toxic (T+), T = Toxic(T), Xn = Harmful (Xn), C = Corrosive (C), Xi = Irritant (Xi), O = Oxidizing (O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment (N)

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

4 | **FIRST AID MEASURES**

4.1 | **DESCRIPTION OF FIRST AID MEASURES**

No harm to the staff authorized to use has been reported. However, in case of contact, inhalation or ingestion, the following general measures provided for a first aid shall be taken.

- EYES & SKIN** Wash with plenty of water; if the irritation persists, seek medical advice.
- INHALATION** Remove to open air. If respiration is difficult, administer artificial respiration and seek medical advice.
- INGESTION** Seek medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.

4.2 | **MOST IMPORTANT SYMPTOMS & EFFECTS, BOTH ACUTE & DELAYED**

No episodes of damage to health ascribable to the product have been reported.



MANUFACTURERS SAFETY DATA SHEET

Faux Real Mineral Paint

- 4.3 | **INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION & SPECIAL TREATMENT NEEDED.**
Follow doctor's orders.
- 5 | **FIREFIGHTING MEASURES**
- 5.1 | **EXTINGUISHING MEDIA**
- SUITABLE EXTINGUISHING MEDIA The extinction equipment should be of the conventional kind: carbon dioxide, foam, powder and nebulized water.
- EXTINGUISHING MEDIA WHICH SHALL NOT BE USED FOR SAFETY REASONS
None in particular.
- 5.2 | **SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE**
HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE
Do not breathe combustion products (carbon oxide, toxic pyrolysis products, etc.).
- 5.3 | **ADVICE FOR FIREFIGHTERS**
- GENERAL INFORMATION Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.
- SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS
Hardhat with visor, fireproof clothing (fireproof jacket and trousers with straps around arms, legs and waist), work gloves (fireproof, cut proof and antistatic), a depressurized mask with facemask covering the whole of the operator's face or a self-respirator (self-protector) in the event of large quantities of fume.
- 6 | **ACCIDENTAL RELEASE MEASURES**
- 6.1 | **PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT & EMERGENCY PROCEDURES**
Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. If there are no contraindications, spray solid products with water to prevent the formation of dust. Use breathing equipment if fumes or powders are released into the air. Block the leakage if there is no hazard. Do not handle damaged containers or the leaked product before donning appropriate protective gear. For information on risks for the environmental and health, respiratory tract protection, ventilation and personal protection equipment, see the other sections of this sheet. These indications apply for both processing staff and those involved in emergency procedures.



MANUFACTURERS SAFETY DATA SHEET

Faux Real Mineral Paint

6.2 | ENVIRONMENTAL PRECAUTIONS

The product must not penetrate the sewers, surface water, ground water and neighboring areas.

6.3 | METHODS & MATERIAL FOR CONTAINMENT & CLEANING UP

Use inert absorbent material (sand, vermiculite, diatomaceous earth, Kieselguhr, etc.) to soak up leaked product. Collect the majority of the remaining material and deposit it in containers for disposal. If there are no contraindications, use jets of water to eliminate product residues. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4 | REFERENCE TO OTHER SECTIONS

Any information on personal protection and disposal is given in sections 8 and 13.

7 | HANDLING & STORAGE

7.1 | PRECAUTIONS FOR SAFE HANDLING

Do not smoke while handling and use.

7.2 | CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Store in a well-ventilated place; keep far away from sources of heat, bright flames and sparks and other sources of ignition.

7.3 | SPECIFIC END USE(S)

Information not available.

8 | EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 | CONTROL PARAMETERS

Name	Type	Country	TWA/8h	STEL/15min
			mg/m ³	ppm mg/m ³ ppm
TALC	TLV-ACGIH		2	
	OEL	IRL	0.8	
	WEL	UK	1	

8.2 | EXPOSURE CONTROLS

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration or bad air vent. If such operations do not make it possible to keep the concentration of the product below the permitted workplace exposure thresholds a suitable respiratory tract protection must be used. See product label for hazard details during use. Personal protection equipment must comply with the rules in force indicated below.



MANUFACTURERS SAFETY DATA SHEET

Faux Real Mineral Paint

HANDLING PROTECTION

Protect hands with category II (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in PVC, neoprene, nitrite or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.

EYE PROTECTION

Wear protective airtight goggles (ref. standard EN 166).

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

RESPIRATORY PROTECTION

If the threshold value (if available) for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an B or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141) The use of respiratory tract protection equipment, such as masks like that indicated above, is necessary to reduce worker exposure in the absence of technical measures. The protection provided by masks is in any case limited.

If the substance in question is odorless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

9 | PHYSICAL & CHEMICAL PROPERTIES

9.1 | INFORMATION ON BASIC PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOR	Color Palette
Odor	Characteristic
ODOR THRESHOLD	-
pH.	-
MELTING OR FREEZING POINT	-
BOILING POINT	-
DISTILLATION RANGE	-
FLASH POINT	> 61°C
EVAPORATION RATE	-
FLAMMABILITY OF SOLIDS & GASES	-
LOWER INFLAMMABILITY LIMIT	-
UPPER INFLAMMABILITY LIMIT	-
LOWER EXPLOSIVE LIMIT	-
UPPER EXPLOSIVE LIMIT	-



MANUFACTURERS SAFETY DATA SHEET

Faux Real Mineral Paint

VAPOR PRESSURE	-
VAPOR DENSITY	-
SPECIFIC GRAVITY	1,370 Kg/l
SOLUBILITY	Water
PARTITION COEFFICIENT: N-OCTANOL/WATER	-
IGNITION TEMPERATURE	-
DECOMPOSITION TEMPERATURE	-
VISCOSITY	-
REACTIVE PROPERTIES	-

9.2 | OTHER INFORMATION

VOC (Directive 2004/42/EC) 0.00 g/l

Matt coatings for interior walls and ceilings. EU limit value for this product (cat. A / a): 75 g/l (2007) / 30g/l (2010).

10 | STABILITY & REACTIVITY

10.1 | REACTIVITY

There are no particular risks of reaction with other substances in normal conditions of use.
CALCIUM CARBONATE Decomposes at temperatures above 800°C.

10.2 | CHEMICAL STABILITY

The product is stable in normal conditions of use and storage.

10.3 | POSSIBILITY OF HAZARDOUS REACTIONS

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4 | CONDITIONS TO AVOID

None in particular, however the usual precautions used for chemical products should be respected.

10.5 | INCOMPATIBLE MATERIALS

CALCIUM CARBONATE Acids

10.6 | HAZARDOUS DECOMPOSITION PRODUCTS

In the event of thermal decomposition or fire, vapors potentially dangerous to health may be released.

CALCIUM CARBONATE Calcium Oxides, Carbon Oxides.

11 | TOXICOLOGICAL INFORMATION

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled according to good industrial practices.



MANUFACTURERS SAFETY DATA SHEET

Faux Real Mineral Paint

11.1 | INFORMATION ON TOXICOLOGICAL EFFECTS

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation
Contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Vapor inhalation may slightly irritate the upper respiratory tract. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

12 | ECOLOGICAL INFORMATION

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

SILICIC ACID, POTASSIUM SALT

LD50 (Oral) > 2000 mg/kg Rat

CALCIUM CARBONATE

LD50 (Oral) 6450 mg/kg Rat

TITANIUM DIOXIDE

LD50 (Oral) > 10000 mg/kg Rat

12.1 | TOXICITY

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil, sewers and waterways. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.2 | PERSISTENCE & DEGRADABILITY

Information not available.

12.3 | BIOACCUMULATIVE POTENTIAL

Information not available.

12.4 | MOBILITY IN SOIL

Information not available.

12.5 | RES DULTS OF PBT & VPVB ASSESSMENT

Information not available.

12.6 | OTHER ADVERSE EFFECTS

Information not available.

13 | DISPOSAL CONSIDERATIONS

13.1 | WASTE TREATMENT METHODS

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.



MANUFACTURERS SAFETY DATA SHEET

Faux Real Mineral Paint

Disposal must be performed through an authorized waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14 | TRANSPORT INFORMATION

The product is no Dt dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

15 | REGULATORY INFORMATION

15.1 | SAFETY, HEALTH & ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

SEVESO CATEGORY None

RESTRICTIONS RELATING TO THE PRODUCT OR CONTAINED SUBSTANCES PURSUANT TO ANNEX XVII TO EC REGULATION 1907/2006.

3

SUBSTANCES IN CANDIDATE LIST (ART. 59 REACH)

None

SUBSTANCES SUBJECT TO authorization (ANNEX XIV REACH)

None

Healthcare controls Not Available.

15.2 | CHEMICAL SAFETY ASSESSMENT

No chemical safety assessment has been processed for the mixture and the substances it contains.

16 | OTHER INFORMATION

Text of hazard (H) indications mentioned in section 2 - 3 of the sheet

EYE IRRIT. 2 Eye irritation, category 2

SKIN IRRIT. 2 Skin irritation, category 2

H319 Causes serious eye irritation.

H315 Causes skin irritation.

TEXT OF RISK (R) PHRASES MENTIONED IN SECTION 2 - 3 OF THE SHEET:

R36/38 Irritating to eyes and skin.



MANUFACTURERS SAFETY DATA SHEET

Faux Real Mineral Paint

GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments
2. Directive 67/548/EEC and following amendments and adjustments
3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
6. Regulation (EC) 453/2010 of the European Parliament
7. The Merck Index. – 10th Edition
8. Handling Chemical Safety
9. Niosh – Registry of Toxic Effects of Chemical Substances
10. INRS – Fiche Toxicology (toxicological sheet)
11. Patty – Industrial Hygiene & Toxicology
12. N.I. Sax – Dangerous properties of Industrial Materials-7, 1989 Edition

NOTE FOR USERS:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability & thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health & safety laws & regulations. The producer is relieved from any liability arising from improper uses.